

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number  
**WO 2005/060862 A1**

(51) International Patent Classification<sup>7</sup>: **A61C 8/00**

(74) Agent: **OLSSON, Gunnar**; Nobel Biocare AB (pub1),  
Box 5190, S-402 26 Göteborg (SE).

(21) International Application Number:  
PCT/SE2004/001553

(22) International Filing Date:  
22 November 2004 (22.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0303461-8 22 December 2003 (22.12.2003) SE

(71) Applicant (for all designated States except US): **NOBEL  
BIOCARE AB (publ)** [SE/SE]; Box 5190, S-402 26 Göte-  
borg (SE).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **BRAJNOVIC, Izidor**  
[SE/SE]; Smörslottsgatan 4, S-416 77 Göteborg (SE).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: METHOD AND ARRANGEMENT FOR ORIENTING A BRIDGE IN POSITION RELATIVE TO A DENTAL IM-  
PLANT



(57) Abstract: In a method for orienting a bridge (3) in position relative to a dental implant (1) with the aid of spacer members, these are brought into cooperation with, on the one hand, the respective implant and, on the other hand, with fastening members (11) arranged in the bridge. A first sleeve-shaped part (9) included in the spacer member is brought into cooperation with the implant (1). A second sleeve-shaped part (10) included in the spacer member is brought into cooperation with, on the one hand, the first sleeve-shaped part and, on the other hand, with a fastening member in the bridge. Said sleeve-shaped parts (9, 10) are made to assume assembled positions when the bridge is anchored to the implants. Upon detachment of the bridge from the implant, the first and second sleeve-shaped parts are separated so that the first sleeve-shaped part can maintain its position on the implant. The second sleeve-shaped part can follow along with the bridge or can constitute a free part. The invention also relates to an arrangement for obtaining said position orientation. By means of the invention, it is possible to reduce the number of components in connection with bridge installations. A good esthetic appearance can be maintained, and it is possible to minimize damage which can cause bone absorption.



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*